PARKWAY ASSOCIATION ENTRY-DOOR STANDARDS

The following rules will apply to any entry-door replaced on initiative of the Owner:

- 1 Maintenance and repair of the new entry-doors replaced by the Owner will be the responsibility of the Owner. This includes repainting when necessary as indicated by the Association.
- 2 Although the Owner has the freedom to choose a door style according to the guidelines included below, he or she MUST request the concurrence of the Association BEFORE the replacement. The process for obtaining the Association's approval is identical to that required for any other exterior improvement.

Guidelines:

- 1. <u>Material:</u> The door material shall be solid wood or fabricated wood or wood-like fiberglass. Steal doors (including wood doors with external steel panels) ARE NOT allowed.
- 2. <u>Style:</u> There are a number of styles presently used in our association. The permitted styles reflect the existing ones:
 - A) Existing single entry-door with a stationary side window (sidelites) MUST be replaced
 with a similar single entry-door with a stationary side window (sidelite). However, an
 additional glass-window on the main door will be acceptable as an option.
 - B) Existing single entry-door without a sidelite MUST be replaced with a single door without a sidelite. However, a glass window on the door will be accepted as an option.
 - C) Existing double-doors can be replaced with a double door or with a single door and two stationary windows (sidelites), one at each side. In both cases, a glass window will be accepted as an option. If a single door is chosen (with two sidelites), the overall width, of the door and sidelites MUST be the same as that of the double door to be replaced.
 - D) The size of the glass window on the door(s) CANNOT be larger than 50% of the size of the entire door.
 - E) Doors with a rounded (arched) top are NOT accepted.
- 3. Color: The accepted colors are:
 - ~ White
 - ~ One of the typical wood colors with prior approval
 - ~ Other than the above two WILL NOT be accepted.
- 4. Glass: If sidelites are used and the main door(s) have windows, then the type of glass used for the sidelites MUST match the type on the door(s) and CANNOT be transparent. If the main door(s) are solid (not window), then the sidelite window can be made of transparent glass or not. In all cases, the glass MUST BE tempered (does not shatter).